



Germanischer Lloyd

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 33 778 - 06 HH

Company Draka Comteq Germany GmbH & Co. KG
Piccoloministr. 2
51063 Köln, GERMANY

Product Description Halogen free foam-PE insulated and FRNC sheathed twisted pairs data transmission cables

Type UC900 SS27 Cat.7; UC900 SS23 Cat.7;
UC1500 SS23 Multimedia (Cat.7)

Environmental Category None

Technical Data / Range of Application UC900 SS27 Cat.7

Conductor: Stranded bare copper wire, (AWG 27/7)
Insulation: Foam skin PE diameter 0,98 mm
Twisting: 2 cores to the pair
Pair screen: Al-laminated plastic foil
Cable lay up: 4 pairs (PIMF) to the core
Screen: Copper braid, tinned
Sheath: FRNC, thermoplastic copolymer (SHF1)

Electrical properties: Loop resistance: $\leq 340 \Omega / km$
Mutal capacitance: Nom. 43 nF/km at 800 Hz
Character. impedance: 100 Ω
More propertiees according to Draka data sheet

Mechanical properties: Temperature range: -20°C to +60°C (operating)
Bending radius: $\geq 25 mm$

Test Standard EN 50173-1:2002; EN 50288-4-2:2003; IEC 11801:2002; IEC 61156-5:2002
IEC 60332-1:1993; IEC 60332-3-24:2000; IEC 60754-2:1997; IEC 61034:1997

Documents Test report : Draka Comteq reference 2006035_DA_summery, dated of 19.09.2006

Remarks None

Valid until 2011-10-09

Page 1 of 2

File No. I.N.01

Hamburg, 2006-10-10

Type Approval Symbol



Germanischer Lloyd

Wolfgang Voß

Reinhard Fenster



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 33 778 - 06 HH

UC900 SS23 Cat.7

Conductor: Bare copper wire, 0,56 mm (AWG 23)
Insulation: Foam skin PE, diameter 1,4 mm
Twisting: 2 cores to the pair
Pair screen: Al-laminated plastic foil
Cable lay up: 4 pairs (PiMF) to the core
Screen: Copper braid, tinned
Sheath: FRNC, thermoplastic copolymer (SHF1)
Electrical properties: Loop resistance: $\leq 150 \Omega / \text{km}$
Mutal capacitance: Nom. 43 nF/km at 800 Hz
Character. impedance: 100 Ω
More propertiees according to Draka data sheet
Mechanical properties: Temperature range: -20°C to +60°C (operating)
Bending radius: $\geq 30 \text{ mm}$

UC1500 SS23 Multimedia

Conductor: Bare copper wire, 0,57 mm (AWG 23)
Insulation: Foam skin PE, diameter 1,4 mm
Twisting: 2 cores to the pair
Pair screen: Al-laminated plastic foil
Cable lay up: 2 x 2 pairs to the core
Screen: Copper braid, tinned
Sheath: FRNC, thermoplastic copolymer (SHF1)
Electrical properties: Loop resistance: $\leq 135 \Omega / \text{km}$
Mutal capacitance: Nom. 43 nF/km at 800 Hz
Character. impedance: 100 Ω
More propertiees according to Draka data sheet
Mechanical properties: Temperature range: -20°C to +60°C (operating)
Bending radius: $\geq 35 \text{ mm}$

Application limitations: The UC900 SS23 and the UC1500 S S23 cable can be used for non-essential data communications.

Place of production: Draka Comteq / Cable Solutions EMEA, Wohlauer Str. 15, D-90475 Nürnberg

Valid until 2011-10-09

Page 2 of 2

Type Approval Symbol



File No. I.N.01

Hamburg, 2006-10-10

Germanischer Lloyd

W. Voß
Wolfgang Voß

R. Fenster
Reinhard Fenster