



1.1/5.0 AF "High Screen" PVC white, BZT-No. G 628 156 C

CATV Drop Cable



Application

Drop cables are used in TV signal distribution networks and as antenna cable for terrestrial and satellite broadcast systems.

Standards

Flame resistance

Construction

Inner conductor	bare copper wire, diameter 1.1 mm
Insulation	phys. foam PE, diameter 5.0 mm
Outer conductor	Al-PETP-Al foil under tinned copper braid, diameter 5.6 mm Optical coverage 80%
Sheath	PVC, diameter 6.8 ± 0.2 mm white

Electrical properties

at 20°C

DC resistance	Inner conductor	19 Ω /km
	Outer conductor	12 Ω /km
Mutual capacitance		55 nF/m
Characteristic impedance		75 $\Omega \pm 3 \Omega$
Velocity ratio		80 %
Screening factor		> 90 dB



1.1/5.0 AF "High Screen" PVC white, BZT-No. G 628 156 C

Electrical data

at 20°C

Frequency (MHZ)	Attenuation (dB/100m)	Return loss (dB)	
		Frequency (MHz)	
5	1.3	5-30	> 26
50	4.0	30-470	> 23
100	5.6	470-862	> 20
200	8.0	862-2150	> 18
400	11.8		
862	18.0		
1000	19.4		
1350	23.5		
1600	25.7		
1750	27.0		
2150	30.5		
2550	33.2		
3000	36.0		

Technical data

Product code	Cable type	Weight kg/km	Copper content	Standard delivery length m	Drum size KTG/ring	Bending radius mm	Tensile force N	Storage
CK2748800	1.1/5.0 AF HS	53	27	1000	071	35	180	inside